

TECHNICAL BULLETIN

TARMAC RALLY TECHNICAL REGULATIONS - MODERN

REFERENCE:

CAMS Online Manual of Motor Sport, Rally Road, Tarmac Rally Technical Regulations – Modern.

http://www.camsmanual.com.au/04_rally_road.asp

RATIONALE:

To provide greater choice in respect of wheel diameter for tarmac rally competitors.

ACTION:

Amend the Tarmac Rally Technical Regulations – Modern as follows:

M1

10. Wheels and Tyres

10.1 Each wheel is free save that the width and diameter of the original shall not be exceeded. ~~After market wheels may replace original wheels save that original dimensions shall be retained.~~

M2

10. Wheels and Tyres

10.1 Each wheel is free save that the width and diameter of the original shall not be exceeded. ~~The wheels are free, save that they must be of the standard diameter and width and offset and comply with Schedule E (refer “General Requirements for Cars and Drivers”).~~

M3

10. Wheels and Tyres

10.1 Wheels and tyres are free subject to the following:

(i) The diameter and width of the wheels shall be no greater than the following dimensions, unless fitted as

original with larger, in which case the **maximum dimensions shall be that of the** standard wheel ~~dimension is able to be utilised:~~

Up to 2000cc corrected engine capacity 16” diameter x 7” width

2000cc – 4000cc corrected engine capacity 17" diameter x 7" width
Over 4000cc corrected engine capacity 17" diameter x 8" width

- (ii) Tyres must be in accordance with the provisions outlined elsewhere in these regulations.
- (iii) Wheels and tyres must be covered by the mudguards.

END